

## SPECIFICATIONS



Model		Dimensions		COM Yards	
FN		Height	18.5"	Total Yards	2.8
<b>Weight</b>		Width	30"	Seat Yards	2.8
Plinth Base	49 lbs				
Steel Base	57 lbs				

\*Intended for indoor use only



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Power (Max of 2), Ganging and Bolt-down.  
Factory Ballasting (*Plinth Base only*) (50 lbs).

\*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A-H and COM. Upholstered flammability standard upgradeable to TB133.

### Fabrication & Material

Constructed of wood, 2.5" thick foam, enclosed wood panel with secure hardware and finished with upholstery. Optional plinth or steel base. Made in the U.S.A.

### Assembly

None required

### Installation

Required for Ganging plates and Bolt-down.

### Warranty

10 year limited replacement warranty.

### Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabric.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Product tested to 750 lb static load
- Meets the requirements of ANSI/BIFMA X5.4-2012