

## SPECIFICATIONS



Model	Weight	Width	Dimensions	
IGS-18-3	2.5 lbs	18"	Height	3.1"
IGS-24-3	3.7 lbs	24"	Depth	3"
IGS-36-3	5.2 lbs	36"		
IGS-42-3	5.9 lbs	42"		
IGS-48-3	6.9 lbs	48"		

\*Intended for indoor use only



## DETAILS

### Options

18", 24", 36", 42" and 48" lengths

### Assembly

Shipped assembled

### Fabrication & Material

3 1/8" dia. 11 gauge type 304 stainless steel flanges are heliarc welded to 1 1/2" O.D. 18 gauge seamless tube. Suicide resistant 11 gauge closure plate is also heliarc welded to edge between tube and wall. Stainless steel #4 finish.

### Installation

Norix only recommends its products to be attached to solid concrete surfaces. For all other applications consult your professional installer for proper attachment. Installation hardware not supplied by Norix.

### Warranty

1 year limited replacement warranty

### Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

## TESTING

### Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

### Performance Test Standards

18", 24", 36" and 42" Grab Bars: Product tested to 250 lbs static load.  
48" Grab Bar: Product tested to 750 lbs static load.